

4



3

2

1

REVISIONS				
ZONE	LTR	DESCRIPTION	DATE	APPROVED

CODE KLIXON®
MADE IN USA
AND TI PART NO.



CHARACTERISTICS

- 1. BASIC THERMOSTAT: 4286 STYLE
- 2. DIELECTRIC STRENGTH: 1250 VAC FOR 1 MINUTE
TERMINALS TO CASE
- 3. MATERIAL: #300 STAINLESS STEEL

NOTES:

- 1. ORIENTATION OF CONNECTOR WITH RESPECT TO DEVICE CENTERLINE IS NOT CONTROLLED.

SEALTRON CONNECTOR
B6002-10SL-4P-F-M126
OR EQUAL

.390 / .360

Ø .072 / .052
HOLE (2-PL)

3/4-16 UNF-3A THREAD

O-RING RECESS

LENGTH TBD
AVAILABLE FROM 1.5" TO 6"
IN 1/2" INCREMENTS

.414 / .394

Ø .665 MAX.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES					THIS IS A CAD DRAWING THE GEOMETRY IN THE ASSOCIATED CAD COMPUTER FILE IS DIMENSIONALLY ACCURATE				
TOLERANCES ON FRACTIONS DECIMALS ANGLES					IF DRAWING IS BEING REVISED THE GEOMETRY MUST BE UPDATED IN ALL VIEWS AND ON ALL SHEETS				
DRAWN S. MARQUIS		DATE 3/25/02		TEXAS INSTRUMENTS ATILEBORO MA 02705			KLIXON CONTROL PRODUCTS DIVISION		
ENGINEER		APPROVED		TITLE THERMOSTAT SWITCH ENVELOPE DRAWING					
MATERIAL		APPROVED		SIZE B		CODE IDENT NO. 82647		21546 STYLE	
SIGNATURES ON FILE. REFER TO ELECTRONIC CHANGE NOTICE.				SCALE			SHEET		

NEITHER THIS PRINT NOR THE INFORMATION CONTAINED THEREON IS TO BE USED AGAINST THE INTEREST OF TEXAS INSTRUMENTS, INC. OR AGAINST THE INTERESTS OF ANY OF ITS AFFILIATED COMPANIES OR WHOLLY OWNED SUBSIDIARIES.

FOR REFERENCE ONLY
CONSULT TEXAS INSTRUMENTS
CUSTOMER SERVICE FOR LATEST
REVISION BEFORE USE

4

3

2

1